




RECOMMENDED PCB LAYOUT

Technical data

- 1 Nominal voltage: 300V/15A (IEC 320V/12A) PITCH:5.0mm
- 2 Insulation Withstands Voltage: AC 1600V/MIN / AC 2500V/MIN
- 3 Insulation Resistace: 1000M Ω or more at DC500V
- 4 Using temperature range:-40C^o ~ 115C^o
- 5 Soldering temperature range:250C^o±10C^o/5sec
- 6 Safety approval:  
- 7 RoHS Compliance
- 8 Critical dimension: 
- 9 Undimensioned Tolerances:

Dim.L=P×5.0	Dim B	Dim L
Dim.B=(P-1)×5.0	±0.15	±0.20
P = number of poles 2-24P	±0.20	±0.25
	±0.25	±0.30
	±0.30	±0.40

HAAH500 XX X XXX

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue:....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
MATERIAL									
DWG	WF: Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK.	WF: Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 (:)	REV.:	A		±0.30
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-AH500 Series open type Right-angle (90D)				
PART NO.		HAAH500xxxxxx			PART NO.		HAA-A500-B002		
DWG NO.		HAA-A500-B002			PART NO.		HAA-A500-B002		
SIGN					DATE				
DESCRIPTION					CHK.				



KUNA CONTACT TECHNOLOGY CO., LTD
http://www.kunacon.com