



Technical data

- 1.Nominal voltage: 300V/15A (IEC 320V/12A) PITCH:5.08mm
- 2.Insulation Withstands Voltage: AC 1600V/MIN / AC 2500V/MIN
- 3.Insulation Resistace: 1000M Ω or more at DC500V
- 4.Using temperature range:-40C ~ 115C
- 5.Soldering temperature range:250C \pm 10C/5sec
- 6.Safety approval:
- 7.Rohs Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim.L=P \times 5.08 \pm 2.0	Dim B	Dim L
Dim.B=(P-1) \times 5.08	0-30mm	\pm 0.15
P = number of poles 2-24P	over 30mm-60mm	\pm 0.20
	over 60mm-90mm	\pm 0.25
	over 90mm	\pm 0.30
		\pm 0.40

HABH508 xx x xxx

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	COPPER	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
ITEM NAME OF PART MATERIAL NOTES									
DWG.	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 3:1 (.)	REV.:	A		
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-BH508 Series Close type X.X Right-Angle (90D) X.XX X ⁺				
PART NO.		HABH508xxxxxx			PART NO.		HA-B508-B002		
DWG NO.		HA-B508-B002			DWG NO.		HA-B508-B002		
SIGN		DESCRIPTION		CHK.	DATE				



KUNA CONTACT TECHNOLOGY CO., LTD
http://www.kunacon.com