



Technical data

- 1. Nominal voltage: 300V/8A (IEC 160V/8A)
PIT CH: 3.5mm
- 2. Insulation Withstands Voltage:
AC1600V/MIN / AC 2500V/MIN
- 3. Insulation Resistance:
1000MΩ or more at DC500V
- 4. Using temperature range: -40°C ~ 115°C
- 5. Soldering temperature range: 250°C ± 10°C / 5sec
- 6. Safety approval:
- 7. RoHS Compliance
- 8. Critical dimension:
- 9. Undimensioned Tolerances:

Dim L=(P-1)X3.5+4.9	Dim B	Dim L
Dim B=(P-1)X3.5	±0.15	±0.20
P = number of poles	±0.20	±0.25
	±0.25	±0.30
	±0.30	±0.40
	±0.30	±0.40

HABV350 xx x xxx

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
MATERIAL									
DWG.	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 (:)	REV.:	A		±0.30
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-BV350 Series Close type				±0.10
PART NO. HABV350xxxxxx					PART NO. HABV350-B001				
DWG NO. HA-B350-B001					DWG NO. HA-B350-B001				
SIGN					DESCRIPTION				
CHK.					DATE				
 KUNA Contact Technology Co. Ltd http://www.kunacon.com									