



Technical data

- 1. Nominal voltage: 300V/8A (IEC 160V/8A)  
PITCH: 3.5mm
- 2. Insulation Withstands Voltage:  
AC1600V/MIN / AC 2500V/MIN
- 3. Insulation Resistance:  
1000MΩ or more at DC500V
- 4. Using temperature range: -40°C ~ 115°C
- 5. Soldering temperature range: 250°C ± 10°C / 5sec
- 6. Safety approval:
- 7. RoHS Compliance
- 8. Critical dimension:
- 9. Undimensioned Tolerances:

	Dim B	Dim L
0-30mm	±0.15	±0.20
over 30mm-60mm	±0.20	±0.25
over 60mm-90mm	±0.25	±0.30
over 90mm	±0.30	±0.40

- HACH350 xx x xxx  
 ① Poles 02-24  
 ② Color  
 0 Black 3 Orange 5 Green 6 Blue.....  
 ③ Custom  
 000 K MARK 00K KUNACON MARK.....

RECOMMENDED PCB LAYOUT

ITEM	NAME OF PART	MATERIAL	NOTES	QTY
3	FLANGE NUT	BRASS		2
2	PIN	BRASS	TIN PLATED	P
1	BODY	PA66 UL94V-0		1

  

DWG	WF	Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance
CHK	WF	Zhang	DATE	2016.03.10	SCALE	NONE 4:1 ( : )	REV	A	X
APP	Marvin Zhang	DATE	2016.03.31	TITLE	HA-CH350 Series W/F type Right-angle(90D)				
PART NO.	HACH350xxxxxx								
DWG NO.	HA-C350-B002								

  

SIGN	DESCRIPTION	CHK	DATE

