



Technical data

- 1 Nominal voltage: 300V/15A
PITCH: 7.62mm
- 2 Insulation Withstands Voltage:
AC 1600V/MIN
- 3 Insulation Resistace:
1000M Ω or more at DC500V
- 4 Using temperature range: -40C $^{\circ}$ ~ 115C $^{\circ}$
- 5 Soldering temperature range: 250C $^{\circ}$ \pm 10C $^{\circ}$ / 5sec
- 6 Safety approval:
- 7 RoHS Compliance
- 8 Critical dimension:
- 9 Undimentioned Tolerances:

Dim L = (P-1) x 7.62 + 18.2	Dim B	Dim L
Dim B = (P-1) x 7.62	0-30mm	± 0.15
P = number of poles 2-16P	± 0.20	± 0.20
	over 30mm-60mm	± 0.25
	over 60mm-90mm	± 0.30
	over 90mm	± 0.40

HABH762 XX X XXX

- ① Poles 02-16
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale gray....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

3	FLANGE NUT	BRASS	TIN PLATED	P	2
2	PIN	COPPER	ALL COLOR	P	1
1	BODY	PA66 UL94V-0			

DWG	W/F: Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	± 0.50
CHK	W/F: Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 (:)	REV:	A		± 0.30
APP	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-CH762 Series W/F type				± 0.10
					Right-angle (90D)				$\pm 1^{\circ}$
				PART NO.	HACH762xxxxxx				
				DWG NO.	HA-C762-B002				

△	SIGN	DESCRIPTION	CHK	DATE

KUNA CONTACT TECHNOLOGY CO., LTD
http://www.kunacon.com