



Technical data
 1.Nominal voltage: 300V/15A (IEC 250V/12A)
 PITCH:5.08mm

2.Insulation Withstands Voltage:
 AC 1600V/MIN / AC 2500V/MIN

3.Insulation Resistance:
 1000MΩ or more at DC500V

4.Using temperature range:-40°C ~115°C

5.Soldering temperature range:250°C±10°C/5sec

6.Safety approval:

7.RoHS Compliance

8.Critical dimension:

9.Undimentioned Tolerances:

Dim L=(P+2)X5.08	Dim B	Dim L
Dim B=(P-1)X5.08	0-30mm	±0.20
P= number of poles	over 30mm-60mm	±0.25
	over 60mm-90mm	±0.30
	over 90mm	±0.40

HACV508 xx x xxx
 ① Poles 02-24
 ② Color
 0 Black 3 Orange 5 Green 6 Blue.....
 ③ Custom
 000 K MARK 00K KUNACON MARK.....

3	FLANGE NUT	BRASS	TIN PLATED	2
2	PIN	COPPER		1
1	BODY	PA66 UL94V-0		1

DWG	WF. Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance
CHK	WF. Zhang	DATE	2016.03.10	SCALE	NONE 3:1 (.)	REV.	A	±0.50
APP	Marvin Zhang	DATE	2016.03.31	TITLE	HA-CV508 Series W/Flange			±0.30
					type Vertical (180D)			±0.10
				PART NO.	HACV508xxxxxx			±1*
				DWG NO.	HA-C508-B001			

APPROVAL	DATE	DESCRIPTION
CHK	DATE	



KUNA Contact Technology Co., Ltd
<http://www.kunacon.com>