



Technical data

- 1.Nominal voltage: 300V/15A  
PITCH:5.08mm
- 2.Insulation Withstands Voltage:  
AC 1600V/MIN
- 3.Insulation Resistace:  
1000M $\Omega$  or more at DC500V
- 4.Using temperature range:-40C $^{\circ}$  ~115C $^{\circ}$
- 5.Soldering temperature range:250C $^{\circ}$  $\pm$ 10C $^{\circ}$ /5sec

- 6.Safety approval: 
- 7.RoHS Compliance
- 8.Critical dimension: 

9.Undimentioned Tolerances:


Dim.L=1/2P $\times$ 5.08 $\pm$ 2.0	Dim B	Dim L
Dim.B=(1/2P-1) $\times$ 5.08	0-30mm	$\pm$ 0.15
P = number of poles 4-48P	over 30mm-60mm	$\pm$ 0.20
	over 60mm-90mm	$\pm$ 0.25
	over 90mm	$\pm$ 0.30
		$\pm$ 0.40

HA-EV508 xx X xxx

- ① Poles 04-48(2 $\times$ 2P-2 $\times$ 24p)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue:....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

3	PIN	COPPER	TIN PLATED	P
2	COVER	PA66 UL94V-0		1
1	BODY	PA66 UL94V-0		1

ITEM	NAME OF PART	MATERIAL	NOTES
DWG	WF. Zhang	DATE 2016.03.10	UNITS: MM SHEET: 1 OF 1
CHK.	WF. Zhang	DATE 2016.03.10	SCALE: NONE 2:1 (.) REV.: A
APP.	Marvin Zhang	DATE 2016.03.31	TITLE: HA-EV508 Series Close type X.X Vertical (180D) X.XX X $^{\circ}$
PART NO.	HA-EV508xxxxxx		
DWG NO.	HA-E508-B002		

APPROVAL	SIGN	DESCRIPTION	CHK.	DATE
				

KUNA Contact Technology Co., Ltd  
http://www.kunacon.com