



Technical data

- 1.Nominal voltage: 300V/15A  
PITCH:5.08mm
- 2.Insulation Withstands Voltage:  
AC 1600V/MIN
- 3.Insulation Resistance:  
1000M $\Omega$  or more at DC500V
- 4.Using temperature range:-40C° ~ 115C°
- 5.Soldering temperature range:250C° $\pm$ 10C°/5sec
- 6.Safety approval:
- 7.RoHS Compliance
- 8.Critical dimension:
- 9.Undimensioned Tolerances:

Dim L	Dim B	Dim L, A, C, D
0-30mm	$\pm 0.15$	$\pm 0.20$
over 30mm-60mm	$\pm 0.20$	$\pm 0.25$
over 60mm-90mm	$\pm 0.25$	$\pm 0.30$
over 90mm	$\pm 0.30$	$\pm 0.40$

HECV508 XX X XXX  
 ① Poles 02-24  
 ② Color  
 ③ Custom  
 000 K MARK 00K KUNACON MARK.....

△	DESCRIPTION	CHK.	DATE

2	PIN	BRASS	TIN PLATED	P
1	BODY	PA66 UL94V-0		1

ITEM	NAME OF PART	MATERIAL	NOTES
DWG	WF- Zhang	DATE 2016.03.10	UNITS: MM SHEET: 1 OF 1
CHK	WF- Zhang	DATE 2016.03.10	SCALE: NONE 3:1 (.) REV: A
APP	Marvin Zhang	DATE 2016.03.31	TITLE: HE-CV508 Series W/Range Vertical (180D)
PART NO.	HECV508XXXXXX		
DWG NO.	HE-C508-B001		

	Tolerance
X	$\pm 0.50$
XX	$\pm 0.30$
XXX	$\pm 0.10$
X*	$\pm 1^{\circ}$



KUNA Contact Technology Co. Ltd  
<http://www.kunacon.com>