



Technical data

- 1.Nominal voltage: 300V/5.5A
PITCH:3.5mm
- 2.Connection capacity:
AWG 22-16
- 3.Insulation Withstands Voltage:
AC 1600V/MIN
- 4.Insulation Resistance:
1000MΩ or more at DC500V
- 5.Stripping length: 9-10mm
- 6.Using temperature range:-40C~115C°
Soldering temperature:250±10C°/75

7.Undimentioned Tolerances:

Dim L=P×3.5+15 Dim B=L-P-1)X3.5 P = number of poles(2-24P)	Dim B	Dim L
0-30mm	+0.15	+0.20
over 30mm-60mm	+0.20	+0.25
over 60mm-90mm	+0.25	+0.30
over 90mm	+0.30	+0.40

8.Safety approval:

9.RoHS Compliance

10.Critical dimension:

SCAF350 XX X XXX

- ① Poles 01-24
- ② Color
0 Black 5 Green 6 Blue 8 Gray 9 White.....
- ③ Custom
000 "K" logo 00K KUNACON logo

4	CONTACT	PHBZ	Tin PLATED	P
3	LEVEL	PA66 UL94V-0	ALL COLOR	P
2	END COVER	PA66 UL94V-0	ALL COLOR	1
1	BODY	PA66 UL94V-0	ALL COLOR	P

ITEM		NAME OF PART		MATERIAL		NOTES	
DWG	WF. Zhang	DATE	2017.09.26	MM	SHEET: 1 OF 1	Tolerance	
CHK.	WF. Zhang	DATE	2017.09.26	SCALE:	NONE 5:1 (.)	REV: A	
APP.		DATE		TITLE:	SC-AF350 Series		
				PART NO.:	SCAF350XXXXXX		
				DWG NO.:	SC-A350-B101		

▲	DESCRIPTION	CHK.	DATE

KUNACON Technology Co. Ltd			
http://www.kunacon.com			