



Technical data

- 1.Nominal voltage: 300V/30A  
PITCH:9.5mm
- 2.Connection capacity:  
AWG 22-10
- 3.Insulation withstands Voltage:  
AC 2500V/MIN
- 4.Insulation Resistance:  
1000MΩ or more at DC500V
- 5.Tightening torque:  
10.0kgf.cm (1.0Nm)
- 6.Screw thread: M3.5  
Screw type: Captive screw
- 7.Using temperature range:-40C ~+115C  
Soldering temperature:250±10C°/5s
- 8.Undimensioned Tolerances:

	Dim B	Dim L
0-30mm	±0.25	±0.25
over 30mm-60mm	±0.30	±0.30
over 60mm-90mm	±0.30	±0.40
over 90mm-180mm	±0.40	±0.50
over 180mm	±0.50	±0.60

- 9.Safety approval:
- 10.RoHS Compliance
- 11.Critical dimension:

ZCAA952 xx x xxx  
 ① Poles 02-24  
 ② Color  
 0 Black  
 ③ Custom  
 000 "K" logo 00K KUNACON logo

ITEM	NAME OF PART	MATERIAL	NOTES	QTY
3	SCREW+WASHER	STEEL	M3.5x0.6, Ni Plated	P
2	CONTACT	BRASS	M3.5x0.6, Tin PLATED	P
1	BODY	PA66 UL94V-0	Black	1

  

DWG.	WF. Zhang	DATE	2016.04.20	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2016.08.03	SCALE:	NONE 2:1 (.)	REV.:	A	±0.50
APP.	WF. Zhang	DATE	2016.08.03	TITLE:	ZC-A952 Series Side contact pin Barrier Terminal Block			±0.30
				PART NO.:	ZCAA952xxxxx			±0.10
				DWG NO.:	ZC-A952-B101			±1°

  

SIGN	DESCRIPTION	CHK.	DATE

KUNA Contact Technology Co, Ltd  
<http://www.kunacon.com>