



Technical data

- 1 Nominal voltage: 150V/8A
- PITCH: 3.5mm
- 2 Connection capacity: AWG 24-16
- 3 Insulation Withstands Voltage: AC 1300V/MIN
- 4 Insulation Resistance: 1000M Ω or more at DC500V
- 5 Stripping length: 9-10mm
- 6 Using temperature range: -40C ~+15C
- 7 Undimentioned Tolerances:

Dim L=(P-1)X3.5+4.2	Dim B	Dim L
Dim B=(P-1)X3.5	0-30mm	± 0.15
P = number of poles	over 30mm-60mm	± 0.20
	over 60mm-90mm	± 0.25
	over 90mm	± 0.30
		± 0.40

- 8 Safety approval:
 - 9 RoHS Compliance
 - 10 Critical dimension:
- PBLD350 XX X XXX
 ① Poles 02-24
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale grey.....
 ③ Custom
 000 K MARK 00K KUNACON MARK.....

ITEM	NAME OF PART	MATERIAL	NOTES
6	WIRE GUARD	Stainless steel	P
5	CONTACT	BRONZE (PbZ)	P
4	LOCKING	PA66 UL94V-0	2
3	LEVEL	PBT UL94V-0	P
2	COVER	PA66 UL94V-0	1
1	BODY	PA66 UL94V-0	1

DWG	WF	Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance
CHK	WF	Zhang	DATE	2016.03.30	SCALE	NONE 3:1 (.)	REV	A	X
APP	Marvin Zhang	DATE	2016.03.30	TITLE	PB-LD350 Series withself-locking flange type				
PART NO.	PBLD350xxxxxx								
DWG NO.	PB-L350-B001								

△	SIGN	DESCRIPTION	CHK	DATE

KUNA Contact Technology Co. Ltd
<http://www.kunacon.com>