



Technical data

- 1.Nominal voltage: 150V/8A
- PITCH:3.5mm
- 2.Connection capacity:
AWG 24-16
- 3.Insulation Withstands Voltage:
AC 1300V/MIN
- 4.Insulation Resistace:
1000MΩ or more at DC500V
- 5.Stripping length: 9-10mm
- 6.Using temperature range:-40C ~+15C °
- 7.Undimentioned Tolerances:

Dim L=(P-1)x3.81+4.2	Dim B	Dim L
Dim B=(P-1)x3.81	±0.15	±0.20
P= number of poles	over 30mm-60mm ±0.20	±0.25
	over 60mm-90mm ±0.25	±0.30
	over 90mm ±0.30	±0.40

8.Safety approval:

9.RoHS Compliance

10.Critical dimension:

PBSSD381 XX X XXX

① Poles 02-24

② Color

③ Custom
0 Black 3 Orange 5 Green 6 Blue 8 Grey.....
000 K MARK 00K KUNACON MARK.....

5	WIRE GUARD	Stainless steel			P
4	CONTACT	BRONZE (PBZ)			P
3	LEVEL	PBT UL94V-0			P
2	COVER	PA66 UL94V-0			1
1	BODY	PA66 UL94V-0			1

DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance	±0.50
CHK.	WF. Zhang	DATE	2016.03.30	SCALE:	NONE 3:1 (.)	REV.:	A		±0.30
APP.	Marvin Zhang	DATE	2016.03.30	TITLE:	PB-SD381 SERIES				

PART NO.	PBSSD381xxxxxx	DWG NO.	PA-S381-B001
KUNA Contact Technology Co. Ltd http://www.kunacon.com			
SIGN	DESCRIPTION	CHK.	DATE