



Technical data

- 1.Nominal voltage: 300V/15A (CAC 250V/24A)
PITCH:5.0mm
- 2.Connection capacity:
AWG 24-12 / 0.2-2.5mm²
- 3.Insulation Withstands Voltage:
AC 1600V/MIN / AC 2500V/MIN
- 4.Insulation Resistance:
1000M Ω or more at DC500V
- 5.Tightening torque:
3.5kgf.cm (3.0Lb-in/0.35N.m) / 0.4Nm
- 6.Screw thread: M2.6
- 7.Stripping length: 5-6mm
- 8 Using temperature range: -40 $^{\circ}$ C - 115 $^{\circ}$ C
Soldering temperature: 250 \pm 10 $^{\circ}$ C / 5s
- 9.Undimen stoned Tolerances:

Dim L=P \times 5.0 Dim B=(P-1) \times 5.0 P = number of poles(2-24p)	Dim B	Dim L
0-30mm	± 0.15	± 0.20
over 30mm-60mm	± 0.20	± 0.25
over 60mm-90mm	± 0.25	± 0.30
over 90mm	± 0.30	± 0.40

10.Safety approval: Pending

11.RoHS Compliance

12.Critical dimension:

DJHM500 xx X xxx

① Poles 02-24

② Color

0 Black 5 Green 6 Blue 8 Pale grey....

③ Custom

100 K MARK 10K KUNACON MARK.....

4	WIRE GUARD	Stainless steel			P
3	SCREW	STEEL	M2.6 \times 0.45, Zn Plated		P
2	CAGE	BRASS	M2.6 \times 0.45, Tin PLATED		P
1	BODY	PA66 UL94V-0	ALL COLOR		1
ITEM NAME OF PART		MATERIAL		NOTES	
DWG	Kobe, Kang	DATE	2016.04.19	MM	SHEET: 1 OF 1
CHK	WF. Zhang	DATE	2016.09.19	SCALE:	NONE 1:1
APP	WF. Zhang	DATE	2016.09.19	TITLE:	DJ-H500-180D Series "+-+" Slot Screw (Square hole)
PART NO.		DJHM500xxxxxx		Tolerance	
DWG NO.		DJ-H500-B001		± 0.50 ± 0.30 ± 0.10 $\pm 1^{\circ}$	

△			
△			
SIGN	DESCRIPTION	CHK	DATE

KUNA Contact Technology Co, Ltd
<http://www.kunacon.com>