





Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.




Technical data

- 1.Nominal voltage: 300V/20A
PITCH:5.08mm
- 2.Connection capacity:
AWG 30-12
- 3. Insulation Withstands Voltage:
AC 1600V/MIN
- 4. Insulation Resistance:
1000MΩ or more at DC500V
- 5. Tightening torque:
4.3Lb-In(5.0kgf.cm / 0.5N.m)
- 6. Screw thread: M3
- 7. Stripping length: 7-8mm
- 8. Using temperature range: -40°C ~ 115°C
Soldering temperature: 250±10°C/5s
- 9. Undimensioned Tolerances:
Dim L=P×5.08
Dim B=(P-1)×5.08
P = number of poles (02-24P)

	Dim B	Dim L
0-30mm	±0.15	±0.20
over 30mm-60mm	±0.20	±0.25
over 60mm-90mm	±0.25	±0.30
over 90mm	±0.30	±0.40

- 10. Safety approval:
- 11. RoHS Compliance
- 12. Critical dimension:

EJHM508 XX X XXX
 ① Poles 02-24
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale gray....
 ③ Custom
 000 K MARK 00K KUNACON MARK....



△	DESCRIPTION	CHK.	DATE

4	CONTACT	BRASS	Tin PLATED	P
3	SCREW	STEEL	M3×0.5, Zn Plated	P
2	CAGE	BRASS	M3×0.5, Ni PLATED	P
1	BODY	PA66 UL94V-0	ALL COLOR	1

DWG. W/F. Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK. W/F. Zhang	DATE 2016.03.31	SCALE: NONE 3:1 (.)	REV.: A	±0.50
APP. Marvin Zhang	DATE 2016.03.31	TITLE: EJ-H508 Series 2-Interlock		±0.30
		180D " " Slot Screw		±0.10
		PART NO. EJHM508XXXXXX		X ⁺
		DWG NO. EJ-H508-B001		±1 ⁺

