



Technical data

- 1.Nominal voltage: 150V/6A
PITCH:2.5mm
- 2.Connection capacity:
AWG 26-18
- 3.Insulation Withstands Voltage:
AC 1600V/MIN
- 4.Insulation Resistance:
1000MΩ or more at DC500V
- 5.Stripping length: 9-10mm
- 6.Using temperature range:-40C ~+115C
Soldering temperature:250±10C/5S
- 7.Undimentioned Tolerances:

Dim L=P×2.5+1.5 Dim B=(P-1)×2.5 P= number of poles(1-24P)		Dim B	Dim L
0-30mm	±0.15	±0.20	±0.25
over 30mm-60mm	±0.20	±0.25	±0.30
over 60mm-90mm	±0.25	±0.30	±0.40
over 90mm	±0.30	±0.40	±0.50

- 8.Safety approval:
- 9.RoHS Compliance
- 10.Critical dimension:

SDVZ250 xx x xxx
 ① Poles 02-24
 ② Color
 ③ Black 5 Green 6 Blue 8 Gray 9 White....
 ④ Custom
 000 "K" logo 00K KUNACON logo

ITEM	NAME OF PART	MATERIAL	NOTES
6	WIRE GUARD	Stainless steel	P
5	Back Single Contact	BRASS	1/2P
4	Front Single Contact	BRASS	1/2P
3	LEVEL	PA66 UL94V-0	P
2	END COVER	PA66 UL94V-0	1
1	BODY	PA66 UL94V-0	P

DWG	WF. Zhang	DATE	2017.08.27	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2017.09.06	SCALE:	NONE 4:1 (:)	REV.:	A	±0.50 ±0.30 ±0.10
APP.		DATE		TITLE:	SD-VZ250 Series 90D wire Inlet (Vertical) 双排交指脚			
PART NO.	SDVZ250xxxxxxx							
DWG NO.	SD-VZ250-B001							

SIGN	DESCRIPTION	CHK.	DATE