



Technical data

- 1.Nominal voltage: 150V/5A
PITCH:2.54mm
- 2.Connection capacity:
AWG 26-18
- 3. Insulation Withstanding Voltage:
AC 1300V/MIN
- 4. Insulation Resistance:
1000MΩ or more at DC500V
- 5.Stripping length: 7-8mm
- 6.Using temperature range:-40C° -15C°

7.Undimensioned Tolerances:

Dim.L=(P-1)×2.54+3.1	Dim B	Dim L
Dim.B=(P-1)×2.54	±0.15	±0.20
P=1/2 Number of poles(04-48)	over 30mm-60mm ±0.20	±0.25
	over 60mm-90mm ±0.30	±0.30
	over 90mm ±0.30	±0.40

- 8.Safety approval:
- 9.RoHS Compliance
- 10.Critical dimension:

- PDFD254 XXX XXX
- ① Poles 2x2P-2x24P
- ② Color
- 0 Black 5 Green 6 Blue G Plae grey....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

REV	SIGN	DESCRIPTION	CHK	DATE

ITEM	NAME OF PART	MATERIAL	NOTES
6	FLANGE SCREW	STEEL	M2.0, Zn PLATED
5	WIRE GUARD	Stainless steel	t=0.25mm
4	CONTACT	BRONZE (PbBz)	t=0.3mm TIN PLATED
3	LEVEL	POM UL94HB	ORANGE
2	COVER	PA66 UL94V-0	ALL COLOR
1	BODY	PA66 UL94V-0	ALL COLOR

DWG	WF. Zhang	DATE	2020.08.27	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2020.12.19	SCALE:	NONE 3:1 (.)	REV:	A	X ±0.50
APP.	DATE	DATE		TITLE:	PD-FD254 Series Double row Plug W/Flange			X ±0.30
				PART NO.:	PDFD254XXXXXX			X ±0.10
				DWG NO.:	PD-F254-B001			X ±1*



KUNA Contact Technology Co., Ltd
http://www.kunacon.com