



Technical data

- 1. Nominal voltage: 300V/8A
- PITCH: 3.5mm
- 2. Insulation Withstands Voltage: AC1600V/MIN
- 3. Insulation Resistance: 1000MΩ or more at DC500V
- 4. Using temperature range: -40°C ~ 115°C
- 5. Soldering temperature range: 250°C ± 10°C / 5sec
- 6. Safety approval:
- 7. RoHS Compliance
- 8. Critical dimension:
- 9. Undimensioned Tolerances:

Dim L=(P-1)X3.5+4.4 Dim B=(P-1)X3.5 P = number of poles	Dim B	Dim L
0-30mm	±0.15	±0.20
over 30mm-60mm	±0.20	±0.25
over 60mm-90mm	±0.25	±0.30
over 90mm	±0.30	±0.40

HADV350 xx x xxx

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P
1	BODY	PA66 UL94V-0		1
ITEM NAME OF PART MATERIAL NOTES				
DWG. W/F. Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK. W/F. Zhang	DATE 2016.03.10	SCALE: NONE 4:1 (:)	REV: A	±0.50
APP. Marvin Zhang	DATE 2016.03.31	TITLE: HA-DV350 Series Latch type		±0.30
		Vertical(180D)		±0.10
		PART NO. HADV350xxxxxx		X°
		DWG NO. HA-D350-B001		±1°

△	SIGN	DESCRIPTION	CHK.	DATE

